

## CAM-4B-36IR

480 TVL, Infrared Bullet Camera, 3.6 mm Lens, Day/Night, 50 ft.



## Analog 480 TV Line Camera Series

Alpha camera series offers a complete line of 1/3" image format digital color CCD cameras. Their high sensitivity and resolution provide superior performance in most environmental conditions. The Alpha cameras are known for their easy installation and features found on more expensive cameras. Alpha Cameras provide optimal picture quality and durability never before seen in cameras of this category and are backed by a 3-year warranty. The series features a wide range of camera styles addressing virtually any type installation and can be used by novices or professionals and can be used by novices or professionals.

## SPECIFICATIONS

CAMERA	
Series	Alpha
Style	Infrared Bullet
Signal System	NTSC/PAL
Horizontal Resolution (D/N)	480 TVL
Image Sensor	1/3" CCD
	NTSC: 768 (H) x 494(V)
Picture Elements	PAL: 752 (H) x 582 (V)
Lens	3.6 mm fixed
FOV Degrees (Horizontal/Vertical)	67.3°(H)/53.1°(V)
Auto Iris	Yes
Min. Illumination (day)	
	Color (day) 0.1 lux f2.0
Min. Illumination (night) IR Beam Distance	B/W (night) 0 lux f2.0
	50 ft.
Infrared	Yes
Day/Night (Electronic)	Yes
True Day/Night	
Scanning System	2:1 interlaced
Signal-to-Noise Ratio	≥48 dB (AGC off)
Synchronization	Internal
Gamma Correction	0.45 approx.
Back Light Compensation	Yes
White Balance	Yes
On-Screen Display	
Extra Spot Monitor Output	
PoUTP	
DNR (Digital Noise Reduction)	
WDR (Wide Dynamic Range)	
IR Cut Filter (Mechanical)	
3 Way Axis Gimbal	
Communication	
ACCESSORIES	
Bracket	Yes
Sun Shield	Yes
Remote Control	
Power Pigtail Lead	
ENVIRONMENTAL	
Operation Temperature	1 4°F to 122°F (-10°C to 50 °C)
Storage Temperature	-4°F to 140°F (-20°C to 60 °C)
Operating Humidity	Up to 95%
Ingress Protection Rating (IEC 60529)	IP66
Weatherproof	Yes
Vandal Proof	
ELECTRICAL	
	C
Video Out	Composite signal 1.0Vp-p/75ohm
Signal Connector	BNC
Input Voltage	12 VDC
Current Draw	250 mA
Power Consumption	3 Watts
PHYSICAL	
Dimensions (W x H x D)	4.6" x 2.2" x 2.4" (118 x 57 x 62 mm)
Weight	1.43 lb (650 g)
Housing Material	Zinc
Housing Color	Silver
Camera Mounting	Wall
REGULATORY	
Regulatory Type	CE, FCC, UL
Warranty (Effective Jan 1, 2009)	
3 Years	



- 480 TVL color infrared bullet camera
- 3.6 mm fixed lens
- Weatherproof (IP66)
- Electronic day/night 50 feet zero lux illumination
- 12 VDC

## **AVAILABLE MODELS**

Part number	Description
CAM-4B-36IR	480TVL, infrared bullet camera, 3.6 mm fixed lens, day/night, auto iris, 12 VDC, 50 ft