

CAM-5D-36DN-VP

550 TVL, Ultra High-Resolution Color Mini Dome Camera, 3.6 mm Fixed Lens, Day/Night, VP



Analog High Resolution Camera Series

Bravo camera series offers superior imaging quality along with a wide selection of superior camera enclosures engineered by Aventura. The Bravo Series cameras have been setting the standards for image perfection. Bravo series cameras excel in challenging low light conditions and are constructed of the finest materials and are ruggedized to withstand the elements. Bravo cameras are available in a variety of lenses and enclosures to meet the requirements of professional CCTV integrators. Most Bravo cameras come with an unprecedented 10-year warranty.

SPECIFICATIONS

CAMERA	
Series	Bravo
Style	Vandal proof dome
Signal System	NTSC/PAL
Horizontal Resolution (D/N)	550 TVL day / 600 TVL night
Image Sensor	1/3" CCD
Picture Elements	NTSC: 768 (H) x 494(V) PAL: 752 (H) x 582 (V)
Lens	3.6 mm fixed
FOV Degrees (Horizontal/Vertical)	67.3° (H)/53.1° (V)
Auto Iris	Yes
Min. Illumination (day)	Color (day) 0.1 lux f1.4
-	
Min. Illumination (night) IR Beam Distance	B/W (night) 0.002 lux f1.4
Infrared	
Day/Night (Electronic)	Yes
True Day/Night	Yes
Scanning System	2: 1 interlaced
Signal-to-Noise Ratio	≥50 dB (AGC off)
Synchronization	Internal
Gamma Correction	0.45 approx.
Back Light Compensation	Yes
White Balance	Yes
On-Screen Display	
Extra Spot Monitor Output	
PoUTP	
DNR (Digital Noise Reduction)	Yes
WDR (Wide Dynamic Range)	====
IR Cut Filter (Mechanical)	
3 Way Axis Gimbal	Yes
Communication	
ACCESSORIES	
Bracket	
Sun Shield	
Remote Control	
Power Pigtail Lead	Yes
ENVIRONMENTAL	
Operation Temperature	1 4°F to 122°F (-10°C to 50 °C)
Storage Temperature	-2 2°F to 140°F (-3 0°C to 60 °C)
Operating Humidity	Up to 95%
Ingress Protection Rating (IEC 60529)	IP66
Weatherproof	Yes
Vandal Proof	Yes
ELECTRICAL	103
	Composite signal 1 0Vn n/7Fshm
Video Out	Composite signal 1.0Vp-p/75ohm BNC
Signal Connector	
Input Voltage	12 VDC
Current Draw	120 mA
Power Consumption	1 Watt
PHYSICAL	
Dimensions (W x H)	3.23 " ø x 2.61" (82 x 66.4 mm)
Weight	0.88 lb (400 g)
Housing Material	Zinc
Housing Color	Black
Camera Mounting	Wall/ceiling/flush/surface
REGULATORY	
Regulatory Type	CE, FCC, UL
Warranty (Effective Jan 1, 2009)	
10 Years	



- 550 TVL color mini dome camera 3.6 mm fixed lens
- Weatherpoof (IP66) & Vandal proof
- True day/night 12 VDC

AVAILABLE MODELS

Part number	Description
CAM-5D-36DN-VP	550 TVL, color mini dome camera, 3.6 mm fixed lens, day/night, vandal proof, weatherproof, 12 VDC



Aventura - World Headquarters

180 Adams Ave. Hauppauge, NY 11788 USA Tel: 631-300-4000 | Fax: 631-434-7000 www.aventuracctv.com

Aventura and the Aventura logo are registered trademarks of Aventura Technologies, Inc.

Specifications subject to change without notice.

©Copyright 2010. All rights reserved