



# VDS-04

## 4 Channel H.264 IP Video/Audio to Analog Output Converter

This IP to Analog decoder features an embedded real-time multi-tasking operating system (RTOS) and an embedded processor, which is completely independent from a PC.

The IP to Analog converter has the functionality to decompress the video and audio signals simultaneously from H.264 feeds transmitted through IP networks and display real-time video and audio on analog monitors. Supports the most popular streaming protocols (RTP/RTCP,RTSP); supports IE browsing; bi-directional voice communication and PTZ Control

### Basic Functions:

- Real-time H.264 high speed hardware decompression
- Multiple security levels for higher system safety
- Supports RS-232/485 interfaces

### Decompression Functions:

- Supports 4 channels CIF or 4 channels 4CIF (NTSC/PAL) signal. Every channel can be real-time hardware-decompressed independently at 30 FPS (NTSC) or 25 FPS (PAL).
- Supports 4CIF (720 x 480), CIF(352 x 240), QCIF (176 x 120) resolution

### Network Functions:

- Support one 10M/100M compatible Ethernet interface
- Supports TCP/IP protocol, parameter settings, real time video & audio previewing, status examination, alarm through network and store the compression bit rate through network
- Support dynamic broadband dialup
- Supports pan-tilt-zoom control and different camera parameters like size of lens and focus
- Supports remote upgrading and maintenance
- RS-485 interfaces support transparent transmission mode
- Control serial devices through the RS-485
- Set video server parameters through the RS-232 serial ports

### SPECIFICATIONS

Video Input	H.264 (RJ45 Ethernet Port)
Video Output	4 BNC (1.0Vp-p, 75Ω)
Resolution	4CIF (720 x 480), CIF(352 x 240), QCIF (176 x 120)
Video Frame Rate	NTSC: 30 FPS PAL: 25 FPS
Bit Rate	32Kbps ~ 8Mbps
Audio Output	4 BNC (1.0Vp-p, 75Ω)
Communication Interface	1 RJ45 10M/100M UTP Network Port 1 RS232 Interface (RJ45) 1 RS485 interface (RJ45) 1 Alarm Input/Output (RJ45)
Alarm in	2 (Terminal Block)
Alarm out	2 (Terminal Block)
Power Supply	100~240 VAC, 6.3 A, 50~60 HZ
Power Consumption	20~42 W
Working Temperature	-1 0°C to +5 0°C
Working Humidity	10%-90 %
Dimension (DxWxH)	9" x 16.5" x 3"
Weight	14.6 lb

### Warranty (Effective Jan 1, 2009)

1 Year

© Aventura Technologies



- Convert H.264 IP video streams to analog output
- Real-time video & audio (30 fps)
- 4 channels of audio & video (720 x 480)
- Supports PTZ cameras

### AVAILABLE MODELS

Part number	Description
VDS-04	H.264 IP audio/video stream decoder, 4 channels of video and audio, 4CIF

© Aventura Technologies

