

VID-3PV111PTT

1 Channel, Modular, Passive, Video Transceiver (3 pairs)

Features:

- Video (one pair) and remote power (3 pairs) transmission over one 4
- pairs CAT5 cable Transmission range up to 300 meters (max)
- BNC for video, power cord for power, RJ45 female output for video and
- power

 Eliminates costly coaxial cables and minimize installation time

 Use with VID-DPV016PTT for 16 channel video, power over professional CAT5 RJ45 connection

SPECIFICATIONS

SPECIFICATIONS		
CONNECTORS		
Video (BNC Connector)	1(1V p-p, 750hms)	
Transmission Interface	RJ45	
Transmission Distance	600 M (B/W), 300 M (COLOR)	
CABLE		
Cable Types	Twisted Pair CAT5 (AWG24)	
ENVI RONMENTAL	CONTROL	
Storage Temperature	-3 0°C to +70 °C	
Operation Temperature	-1 0°C to +45 °C	
POWER		
Power Source	Passive	
PHYSICAL & MEA	SUREMENTS	
Material	PVC Black	
Dimensions	69 x 25 x 22 mm	
Weight	70 (g)	
Warranty (Effect	ive Jan 1, 2009)	
1 Year		



- Seamless video and power Transmission Supports 24 VAC cameras up to 1000 ft Convenient modular design
- Integrated RJ-45 connector
- Compatible with other Transceivers

AVAILABLE MODELS

Part number	Description
VID-3PV111PTT	1-Channel, Modular, Passive, Video Transceiver supporting 24 VAC (on 3 pairs) Camera Power over Category-type cable

